

PHP



alles rund um das Thema PHP und programmieren

Damit beim Entwickeln auch alle Fehler angezeigt werden, sollte eine .htaccess Datei mit folgenden Einträgen im Verzeichnis sein wobei display_errors on das wichtigste ist.

.htaccess

```
php_flag display_startup_errors on
php_flag display_errors on
php_flag html_errors on
php_value error_reporting 2047
php_flag log_errors on
php_value error_log /home/path/public_html/domain/PHP_errors.log
```

Im PHP Script folgendes:

```
// Melde alle PHP Fehler (siehe Changelog)
error_reporting(E_ALL);
```

Zusammenfassung:

.htaccess

```
# PHP error handling for production servers
# Disable display of startup errors
php_flag display_startup_errors off

# Disable display of all other errors
php_flag display_errors off

# Disable HTML markup of errors
```

```
php_flag html_errors off

# Enable logging of errors
php_flag log_errors on

# Disable ignoring of repeat errors
php_flag ignore_repeated_errors off

# Disable ignoring of unique source errors
php_flag ignore_repeated_source off

# Enable logging of PHP memory leaks
php_flag report_memleaks on

# Preserve most recent error via php_errormsg
php_flag track_errors on

# Disable formatting of error reference links
php_value docref_root 0

# Disable formatting of error reference links
php_value docref_ext 0

# Specify path to PHP error log
php_value error_log /home/path/public_html/domain/PHP_errors.log

# Specify recording of all PHP errors
# [see footnote 3] # php_value error_reporting 999999999
php_value error_reporting -1

# Disable max error string length
php_value log_errors_max_len 0

# Protect error log by preventing public access
<Files PHP_errors.log>
    Order allow,deny
    Deny from all
    Satisfy All
</Files>
```

Absoluten Path

PHP

```
<?php
    echo $_SERVER["DOCUMENT_ROOT"]
?>
```

From:
<https://wiki.hennweb.de/> - **HennWeb**

Permanent link:
<https://wiki.hennweb.de/doku.php?id=programmieren:php:start&rev=1590161928>

Last update: **22/05/2020 16:38**

